

DMS24E Part No : 21000-C1GG0



MSRP : \$ 68.50

General	Features & Benefit	Technical Data	Cross Reference																											
		<table border="1"> <tr> <td></td> <td>DMS24E</td> </tr> <tr> <td>SIZE</td> <td>24</td> </tr> <tr> <td>STROKE</td> <td>3" / (76.2mm)</td> </tr> <tr> <td>Wt. lb (kg)</td> <td>8.8 lb (4kg)</td> </tr> <tr> <td>1</td> <td>5.11"/130mm</td> </tr> <tr> <td>2</td> <td>4.50"/114.5±3mm</td> </tr> <tr> <td>3</td> <td>1.54±0.05" (39±1.3mm)</td> </tr> <tr> <td>4</td> <td>10±0.100" (254±2.54mm)</td> </tr> <tr> <td>5</td> <td>4.75±0.04" (120.7±1mm)</td> </tr> <tr> <td>6</td> <td>3.46±0.1" (87.9±3mm)</td> </tr> <tr> <td>7</td> <td>7.34±0.1" (186.4±3mm)</td> </tr> <tr> <td>A (PORT)</td> <td>3/8-18NPTF</td> </tr> <tr> <td>B (MTG BOLT)</td> <td>5/8-11-UNC-2A</td> </tr> <tr> <td>C (P/ROD)</td> <td>5/8-18-UNF-2A</td> </tr> </table>		DMS24E	SIZE	24	STROKE	3" / (76.2mm)	Wt. lb (kg)	8.8 lb (4kg)	1	5.11"/130mm	2	4.50"/114.5±3mm	3	1.54±0.05" (39±1.3mm)	4	10±0.100" (254±2.54mm)	5	4.75±0.04" (120.7±1mm)	6	3.46±0.1" (87.9±3mm)	7	7.34±0.1" (186.4±3mm)	A (PORT)	3/8-18NPTF	B (MTG BOLT)	5/8-11-UNC-2A	C (P/ROD)	5/8-18-UNF-2A
	DMS24E																													
SIZE	24																													
STROKE	3" / (76.2mm)																													
Wt. lb (kg)	8.8 lb (4kg)																													
1	5.11"/130mm																													
2	4.50"/114.5±3mm																													
3	1.54±0.05" (39±1.3mm)																													
4	10±0.100" (254±2.54mm)																													
5	4.75±0.04" (120.7±1mm)																													
6	3.46±0.1" (87.9±3mm)																													
7	7.34±0.1" (186.4±3mm)																													
A (PORT)	3/8-18NPTF																													
B (MTG BOLT)	5/8-11-UNC-2A																													
C (P/ROD)	5/8-18-UNF-2A																													

 || | | | |
| **Note** - DIMENSION "4" MEASURED WITH MAIN SPRING COMPRESSED PNEUMATICALLY - PRODUCT PERFORMANCE MEET SAE J2318 STANDARD. - PRODUCT COMPLIANCE TO FMVSS121 REGULATIONS | | | |